

## **Mesh Partitioning System**

The Mesh Partitioning System is an integrated partition system suitable for a wide range of applications such as storage areas, dividing work areas and protecting products, property & people.

The system is quick and easy to construct and has a comprehensive range of single, double and sliding doors available. These can be fitted with most types of locks and latches. The panels are bolted to the floor which means it has the added benefit of being demountable and re-locatable with a minimum of effort. Our standard range comes in a wide variety of width options; however standard configurations do not always fit into required spaces, therefore the non-standard or bespoke design is always an option.

### **Key Features**





















Suitable for storage areas Protection

Demountable Comprehensive & relocatable door options

omprehensive Quick & easy door options construction

Powder coated or Galvanised

ted Standard & ed bespoke panel options available

Ceiling solutions

Robust & durable



E: <u>sales@storwellsystems.co.uk</u> T: <u>01527 592 444</u>

www.storwellsystems.co.uk

Systems House, Burnt Meadow Road, Redditch, Worcestershire, B98 9PA

- Mesh Partitioning
  - Security Cages
    - Single Skin Partitioning
  - Double Skin Partitioning 🕠
- Anti-Collapse Mesh Systems
- Barrier Systems
- g Mesh Shelves
  - Ceiling Systems

# **Materials**

The panels are manufactured from cold rolled mild steel angle and cold rolled tees, weld mesh in-fill sheets spot welded together. Panels are bolted together using M8 bolts and floor fixed with pan head screws in 6mm plastic plugs.

Support mullions are manufactured from rectangular hollow section with a 8mm thick base-plate welded to the base of the mullion for floor fixing. Each mullion has a series of drilled and tapped holes along its height ready to receive M8 fixing bolts to position the panels. All mullions are floor fixed with 12mm anchor bolts. The top edges of the panels are aligned with the top cap which is manufactured from a channel section and is generally 3.66m long.

rop channel rop angle

Side angle

Dado Tee

Bottom angle

Mullion

Panel width

How the System Works

**Product Specification** 

The mesh partitioning system is constructed in a formation of panels, support mullions and top capping. The support mullions are positioned at a maximum of 3.7m centres with generally 3 standard panels between and a single top cap connecting the 3 panels together. Once all of these components are bolted together they provide a rigid partition wall up to 3.66m high. Double lift applications above 3.66m are available – please contact our sales team for

## **More Information**

#### **Sections**

- Top & Bottom Angle: 42 x 38 x 1.5mm Side Angle: 40 x 40 x 1.5mm Dado Tees: 42 x 32 x 0.7mm

### **Paint Finish**

#### **Doors & Glazing**

- Single Doors: 915mm wide x 1980mm high Double Doors: 1806mm wide x 1980mm high Door Fittings: 3 Lever locks with aluminium





E: <u>sales@storwellsystems.co.uk</u> T: 01527 592 444 www.storwellsystems.co.uk

Systems House, Burnt Meadow Road, Redditch, Worcestershire, B98 9PA

- Mesh Partitioning
  - Security Cages
- Anti-Collapse Mesh Systems
- Barrier Systems
- Single Skin Partitioning

further information.

- Double Skin Partitioning •
- Mesh Shelves
- Ceiling Systems